

MAXI \* TRACK

# Single-Double Use Data Logger Model Wise-USB- 90-Twice (2 Trips)

Temperature Data Logger with  
external sensor and LCD Display

## Single-Double Use

Range:  
-196 to +200 °C

Accuracy:  
 $\pm 0,5$  °C (-90 +70 °C) /  $\pm 1,0$  °C (rest of the Range)

Memory: 35,000 readings

Insulation: IP-65

External probe built for use in  
Dry Ice or Liquid Nitrogen



**Compliance:**  
21 CFR Parte 11  
CE Mark  
EN 12.830



MAXI \* TRACK

MaxiTrack Sensors

info@maxitracksensors.com | www.maxitracksensors.com

# WISE-USB-90-TWICE

The **Wise-USB-90-Twice** model is a Single-Double Use Temperature Data Logger, reliable, economical, and ideal for transportation and storage in applications within the Health/Pharmaceutical and Food sectors. It has a detachable external probe with a metal rod and silicone cable suitable for extreme temperatures.

External probe: 1.95 (m)

Rod: stainless steel, 120 (mm)

**LCD Display:** View temperatures in real-time and know the Average, Min, and Max values reached before accessing the Report.

## **Programming Features and Statistical Information:**

The final PDF Report provides: total time, number of recordings made, start and end time, recording interval, MIN/MAX/AVERAGES reached, date and time of alarm events, Firmware version, event marking, serial number, and model of the Data Logger, among other information.

**Visual Alarms:** The Data Loggers from the **Wise** / Single-Double Use line can be programmed with alarm limits (visual type). If the temperature reaches levels outside these limits, the LCD Display will show a specific icon indicating that it operated outside the configured critical range. To start recordings, just press the START button!

Single-Double Use Model (Single-Double Use) programmed for one or two trips. The first programming can be used to receive Accredited Calibration before final shipment!



**Compliance:**  
21 CFR Parte 11  
CE Mark  
EN 12.830

---

MAXI \* TRACK

MaxiTrack Sensors

info@maxitracksensors.com | www.maxitracksensors.com

# WISE-USB-90-TWICE

Model	Wise-USB-90-Twice	Type of Use	Single-Double Use
Temperature Range	-196 +200 °C	Temperatura Accuracy	±0.5 °C (between -90 +70 °C) ±1 °C (rest of te range)
Resolution	0.1 °C	Memory Capacity	35.000 readings for PDF file
Report Format	PDF/CSV	Battery Life	Up to 180 days (configurable)
Report Output	Automatic, no software needed	Connection	USB
Compatible OS	Windows / Mac iOS	Logging Interval	1 minute ~ 24 hours
Start Delay	0 minutes ~ 24 hours	Protection Grade	IP-65
Battery	CR2450	Parameters Configurable	Yes
Dimensions	82 x 39 x 13.5 (mm)	Weight	29.3 g
LCD Screen Display	Current Temperature, MAX/MIN/AVG, Alarm Signal, Battery Security Level		



**Compliance:**  
 21 CFR Parte 11  
 CE Mark  
 EN 12.830