

MAXI * TRACK

Single-Double Use Data Logger Model Wise-USB-RH-Twice (2 Trips)

Temperature and Humidity Data
Logger with internal sensor and
LCD Display

Single-Double Use

Range:

-30 to +70 °C / 0~100 %RH

Accuracy:

+/- 0,5 °C (between -30 and +70°C)

+/- 3% RH

Memory: 35,000 readings

Insulation: IP-65



Compliance:
21 CFR Parte 11
CE Mark
EN 12.830

MAXI * TRACK

MaxiTrack Sensors

info@maxitracksensors.com | www.maxitracksensors.com

WISE-USB-RH-TWICE

The **Wise-USB-RH-Twice** model is a reliable and economical Temperature and Relative Humidity Data Logger, ideal for transportation and storage in applications within the Health/Pharmaceutical and Food sectors. It has an internal sensor element and can measure temperatures in the range of -30 to +70 °C and Humidity from 0 to 100 %RH.

LCD Display: View temperatures in real-time and know the Average, Min, and Max values reached before accessing the Report.

Features / Software: The internal software records the following parameters: time, start time, recording intervals, final description for special instructions, alarm values, recording status, measurement data, software version, serial number, and model of the Data Logger.

Visual Alarms: All our loggers can be programmed with alarm limits. If the temperature reaches levels outside these limits, the LCD Display will show a specific icon indicating that it operated outside the configured critical range. To start recordings, just press the START button!

Single-Double Use Temperature/Humidity Data Logger (Single/Double Use), programmed for one or two trips. Enabled to receive Accredited Calibration before shipment!



Compliance:
21 CFR Parte 11
CE Mark
EN 12.830

MAXI * TRACK

MaxiTrack Sensors

info@maxitracksensors.com | www.maxitracksensors.com

WISE-USB-RH-TWICE

Model	Wise-USB-RH-Twice	Type of Use	Single-Double Use
Temperature Range	Temperature: -30 +70°C Humidity: 0~100%RH	Temperatura Accuracy	Temperature ± 0.5 °C (between -30 +70°C) Humidity: $\pm 3\%$ RH
Resolution	Temperature: 0.1 °C Humidity: 0.1%RH	Memory Capacity	35.000 readings for PDF file
Report Format	PDF/CSV	Battery Life	Up to 180 days (configurable)
Report Output	Automatic, no software needed	Connection	USB
Compatible OS	Windows / Mac iOS	Logging Interval	1 minute ~ 24 hours
Start Delay	0 minutes ~ 24 hours	Protection Grade	IP-65
Battery	CR2032	Parameters Configurable	Yes
Dimensions	82 x 39 x 13.5 (mm)	Weight	29.3 g
LCD Screen Display	Current Temperature, MAX/MIN/AVG, Alarm Signal, Battery Security Level		



Compliance:
21 CFR Parte 11
CE Mark
EN 12.830

MAXI TRACK

MaxiTrack Sensors

info@maxitracksensors.com | www.maxitracksensors.com