

MAXI \* TRACK

# Single-Double Use Data Logger Model Wise-USB-Twice (2 Trips)

Temperature Data Logger with Internal Sensor and LCD Display

Single-Double Use



Range:  
-30 +70 °C

Accuracy:  
+/- 0.5 °C (between -30 and +70 °C)

Memory: 35,000 readings

Insulation: IP-65



**Compliance:**  
21 CFR Parte 11  
CE Mark  
EN 12.830

MAXI \* TRACK

MaxiTrack Sensors

info@maxitracksensors.com | www.maxitracksensors.com

# WISE-USB-TWICE

The **Wise-USB-Twice** model is a reliable and economical Temperature Data Logger, ideal for transportation and storage in applications within the Health/Pharmaceutical and Food sectors. It has an internal sensor element and can measure temperatures in the range of -30 to +70 °C.

**LCD Display:** View temperatures in real-time and know the Average, Min, and Max values reached before accessing the Report.

**Features / Software:** The internal software records the following parameters: time, start time, recording intervals, final description for special instructions, alarm values, recording status, measurement data, software version, serial number, and model of the Data Logger.

**Visual Alarms:** All our loggers can be programmed with alarm limits. If the temperature reaches levels outside these limits, the LCD Display will show a specific icon indicating that it operated outside the configured critical range. To start recordings, just press the START button!

Single-Double Use Temperature Data Logger (Single/Double Use), programmed for one or two trips. Enabled to receive Accredited Calibration before shipment!



**Compliance:**  
21 CFR Parte 11  
CE Mark  
EN 12.830

MAXI \* TRACK

MaxiTrack Sensors

info@maxitracksensors.com | www.maxitracksensors.com

# WISE-USB-TWICE

<b>Model</b>	Wise-USB-Twice	<b>Type of Use</b>	Single-Double Use
<b>Temperature Range</b>	-30 +70 °C	<b>Temperatura Accuracy</b>	±0.5 °C (between -30°C +70°C)
<b>Resolution</b>	0.1 °C	<b>Memory Capacity</b>	35.000 readings for PDF file
<b>Report Format</b>	PDF/CSV	<b>Battery Life</b>	Up to 180 days (configurable)
<b>Report Output</b>	Automatic, no software needed	<b>Connection</b>	USB
<b>Compatible OS</b>	Windows / Mac iOS	<b>Logging Interval</b>	1 minute ~ 24 hours
<b>Start Delay</b>	0 minutes ~ 24 hours	<b>Protection Grade</b>	IP-65
<b>Battery</b>	CR2032	<b>Parameters Configurable</b>	Yes
<b>Dimensions</b>	82 x 39 x 13.5 (mm)	<b>Weight</b>	29.3 g
<b>LCD Screen Display</b>	Current Temperature, MAX/MIN/AVG, Alarm Signal, Battery Security Level		



**Compliance:**  
 21 CFR Parte 11  
 CE Mark  
 EN 12.830

**MAXI \* TRACK**

MaxiTrack Sensors

info@maxitracksensors.com | www.maxitracksensors.com